

MAINTENANCE-FREE MOTORCYCLE BATTERY

KT7B-FA (12V6.5Ah)






CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		6.5Ah
Cold Cranking Performance Amps@0°F (-18°C)		90A
Dimension (±2mm)	Length	150mm(5.91inches)
	Width	66mm(2.60inches)
	Container Height	93mm(3.66inches)
	Total Height	93mm(3.66inches)
Battery (with acid)	Approx Weight	2.3kg(5.07lbs)
Terminal type		A
Battery type	Factory Activated Series	
Full Charge	Constant-Voltage Charge:	
	Initial charging current	Less than 0.3C_{10}
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Charge:	
	Charging current 0.1C_{10}, when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	Unlimited
	Voltage	13.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)



GENERAL FEATURES

- Maintenance-free
- Sealed and non-spillable AGM battery
- Shipped pre-charged and ready to install

*Values are subject to variation of +/- 5% in normal manufacturing processes.

Publication No.:LB-KT7B-FA-PD-101659-V1.0-20251215